




<b>SPECIFICATION SHEET NO.</b>	S0427- ESD0302TLOS32L	
<b>ORIGINAL MFG/PART NO.</b>	MDD Diodes/ESD0302TL/SOT23302TLS32L	
<b>NEXTGEN PART CODE</b>	ESD0302TLOS32L	Indicate This Code For <a href="#">RFQ</a> /Order
<b>DATE</b>	Apr. 27, 2025	
<b>REVISION</b>	A3	Updated With Most Recent Data
<b>DESCRIPTION AND MAIN PARAMETRICS</b>	<p>SMD Plastic-Encapsulate ESD Protection Diodes, ESD03 Series, 3 Pads</p> <p>Case SOT-23, Ultra -Low Capacitance, Bidirectional Type</p> <p>Reverse Working Voltage: 3.3V,</p> <p>Clamping Voltage 10VC Max.@1.0A</p> <p>Operating Junction Temp. Range -55°C ~+125°C</p> <p>Package in Tape/Reel, 3,000pcs/Reel</p> <p>RoHS/RoHS III compliant, RoHS Annex III lead Exemption (Exempt per RoHS EU 2015/863) and Halogen Free (HF)</p>	
<b>CUSTOMER</b>		
<b>CUSTOMER PART NUMBER</b>		
<b>CROSS REF. PART NUMBER</b>		
<b>MEMO</b>		


<b>VENDOR APPROVE</b>			
Issued/Checked/Approved			
Effective Date: Apr. 27, 2025			

<b>CUSTOMER APPROVE</b>
Date:

## DESCRIPTION

ESD0302TL is an ultra-low-capacitance Transient Voltage Suppressor (TVS) designed to provide electrostatic discharge (ESD) protection For high-speed data interfaces.

With typical capacitance of 0.2pF (I/O to I/O) only, ESD0302TL is designed to protect parasitic-sensitive systems against over voltage and over-current transient events. It complies with IEC 61000-4-2 (ESD), Level 4 ( $\pm 15\text{kV}$  air,  $\pm 8\text{kV}$  contact discharge), IEC 61000-4-4 (electrical fast transient - EFT) (40A, 5/50 ns), very fast charged device model (CDM) ESD and cable discharge event (CDE), etc. ESD0302TL uses ultra-small SOT-23 package. Each ESD0302TL device can protect two high-speed data lines. The combined features of low capacitance, small size and high ESD robustness make ESD0302TL ideal for high-speed data port and high-frequency line applications, The low clamping voltage of the ESD0302TL guarantees a minimum stress on the protected IC.



*Image shown is a representation only. Exact specifications should be obtained from the product dimension.*



## MAIN FEATURE

- Peak Power Dissipation 56W (8/20 $\mu\text{s}$ )
- Transient Protection For High-Speed Data Lines
- IEC61000-4-2 (ESD)  $\pm 15\text{kV}$  (Air),  $\pm 8\text{kV}$  (Contact)
- IEC61000-4-4 (EFT) 40A (5/50ns) Cable Discharge Event (CDE)
- Protects two Data Line
- Low Clamping Voltage
- Low Leakage Current
- Low Capacitance 0.2pF Typical (I/O - I/O)
- Meet MSL 1 Requirement
- Cross Competitors Parts and More
- RoHS/RoHS III compliant, RoHS Annex III lead Exemption (Exempt per RoHS EU 2015/863) and Halogen Free (HF)

## APPLICATION

- Serial ATA
- Desktops, Servers and Notebooks
- Cellular Phone
- MDDI Ports / USB Data Line Protection
- Display Port
- Digital Visual Interfaces (DVI)

## ELECTRICAL CHARACTERISTICS

- See Page 5 ~Page 6.
- All Parameters are Subject To NextGen Components' Final Confirmation

## HOW TO ORDER

- Please Follow Up Part Code Guide And Indicate NextGen Part Code ESD0302TLOS32L For RFQ and Order.


## PART CODE GUIDE

**RFQ**  
[Request For Quotation](#)


CODE	NAME	KEY SPECIFICATION OPTION
ESD03	Product Series Code	SMD Plastic-Encapsulate ESD Protection Diode, 3 Pads Case SOT-23, Ultra Low Capacitance
02TL	Parameters Code	Letter or Digits (A~Z, a~z or 1~9)
0S	Internal Control Code	Letter or Digits (A~Z, a~z or 1~9)
32L	Marking Code	Marking "32L"
XX	Special/Custom Parameters Code	Letter or Digits (A~Z, a~z or 1~9) for Special Parametric; Blank: N/A

**DIMENSION**- Unit: mm, Case SOT-23 Outline


Top View



Side View



Side View






SYMBOL	DIMENSION (MM)		
	MIN.	TYP.	MAX.
A	0.65		1.40
A1	0.00		0.20
b	0.30		0.55
c	0.08		0.20
D	2.70		3.10
E	1.15		1.65
E1	2.10		2.80
e	1.70		2.10
L	0.15		0.50
L1	0.35		0.70
$\theta$	0°		12°

Recommend Pad Layout (unit : Inch/mm)

Pin Configuration

Circuit Diagram



## MECHANICAL CHARACTERISTICS

CASE	FLAMMABILITY RATING	TERMINALS	MARKING
JEDEC SOT-23 molded plastic body	UL 94V-0	Matte tin plated, High temperature soldering guaranteed: 260°C/10s	32L


## ABSOLUTE MAX. RATING & CHARACTERISTICS - TA=25°C unless otherwise specified, For Reference Only

PARAMETER	SYMBOLS	VALUE	UNITS
ESD per IEC 61000-4-2 (Air)	VESD	±20	KV
ESD per IEC 61000-4-2 (Contact)	VESD	±20	KV
Peak Pulse Power @8/20μs	PPP	56	W
Operating Temperature Range	TOPT	-55 ~+ 125	°C
Storage Temperature Range	TSTG	-55 ~ +150	°C
Lead Solder Temperature- Max. (10 s Duration)	TL	260 /10s	°C


**ELECTRICAL CHARACTERISTICS** - TA=25°C unless otherwise specified, For Reference Only

PARAMETER	TEST CONDITION	SYMBOLS	VALUE			UNITS
			MIN.	TYP.	MAX.	
Reverse Working Voltage	I/O to Ground	VRWM			3.3	V
Reverse Breakdown Voltage	IT = 1.0mA Between I/O and GND	VBR	4.2			V
Reverse Leakage Current	VRWM = 3.3V Between I/O and GND	IR			100	nA
Clamping Voltage	IPP = 1A, tp = 8/20μs Between I/O and GND	VC			10	V
	IPP = 4A, tp = 8/20μs Between I/O and GND				14	V
Forward Voltage	IT = 10mA, tp = 8/20μs Between I/O and GND	VF			1.2	V
Total Capacitance	VR = 0 V, f = 1.0MHz Between I/O and GND	CT		0.4		pF
	VR = 0 V, f = 1.0MHz Between I/O and I/O			0.2		

**RATINGS AND CHARACTERISTICS CURVES**- For Reference Only,  $T_a=25^{\circ}\text{C}$  Unless Otherwise Specified.




**Pulse Waveform**



**Power Derating Curve**


**RECOMMENDED SOLDERING PARAMETERS – FOR REFERENCE ONLY**





PROFILE FEATURE		PB-FREE ASSEMBLY
Average Ramp-up Rate ( $T_L$ Max to $T_p$ )		3°C/second Max
Preheat	Temperature Min ( $T_s$ Min.)	150°C
	Temperature Max ( $T_s$ Max.)	200°C
	Time ( $t_s$ Min. to $t_s$ Max.)	60 ~ 180 seconds
Time maintained above	Temperature ( $T_L$ )	217°C
	Time ( $t_L$ )	60 ~ 150 seconds
Peak/Classification Temperature ( $T_p$ )		260 °C
Time within 5°C of actual Peak Temperature ( $t_p$ )		10 seconds Max.
Ramp-down Rate		6 °C /Second Max.
Time 25 °C to Peak Temperature		8 Minutes Max.
Suggest reflow times		3 Times Max.



**TAPE/REEL** - Unit: mm, All Devices are packed in accordance with EIA standard RS-481-A and specifications



Case	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.5	1.75	3.5	4.0	4.0	2.0	8.0



Reel Size	D	D1	D2	G	H	I	W1	W2	Qty. (pcs)
7"	Ø178	54.4	13.0	R78.0	R25.6	R6.5	9.5	12.3	3000

## IMPORTANT NOTES AND DISCLAIMER

1. **ROHS COMPLIANCE:** The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU RoHS Directive (EU) 2015/863 EC (RoHS3). RoHS Test Report for this product can be obtained at Download Center.
2. **REACH COMPLIANCE:** REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, REACH Test Report for this product can be obtained at Download Center.
3. All Product parametric performance is indicated in the Electrical Characteristics for the listed herein test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.
4. NextGen Component, Inc (*NextGen*) reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
5. *NextGen* makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does *NextGen* assume any liability for application assistance or customer product design.
6. *NextGen* does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application. No license is granted by implication or otherwise under any intellectual property rights of NextGen.
7. *NextGen* products are not authorized for use as critical components in life support devices or systems without express written approval by *NextGen*.
8. *NextGen* requires that customers first obtain an RMA (Returned Merchandise Authorization) number prior to returning any products. Returns must be made within 30 days of the date of invoice, be in the original packaging, unused and like-new condition. At the time of quoting or purchasing, a product may say that it is Non-Cancelable/ Non-Returnable (NCNR). These products are not returnable and not refundable.