

SPECIFICATION SHEET NO.	S0502- ESD3Z5V0CMLS3M	
ORIGINAL MFG/PART NO.	LGE Diodes/ESD3Z5.0CM-L/ESD3Z5V0CMS03M	
NEXTGEN PART CODE	ESD3Z5V0CMLS3M	Indicate This Code For RFQ /Order
DATE	May 2, 2025	
REVISION	A3	Updated With Most Recent Data
DESCRIPTION AND MAIN PARAMETRICS	SMD Transient Voltage Suppressor (TVs) Diodes, ESD3Z Series, Case SOD-323, 2 Pads, Ultra -Low leakage, Bi-Directional Type Reverse Working Voltage : 5.0V, Clamping Voltage 9.8VC Max.@1.0A Operating Junction Temp. Range -55°C ~+125°C Package in Tape/Reel, 3000pcs/Reel RoHS/RoHS III compliant, RoHS Annex III lead Exemption (Exempt per RoHS EU 2015/863) and Halogen Free (HF)	
CUSTOMER		
CUSTOMER PART NUMBER		
CROSS REF. PART NUMBER		
MEMO		

VENDOR APPROVE

Issued/Checked/Approved



Effective Date: May 2, 2025

CUSTOMER APPROVE

Date:

MAIN FEATURE

- Ultra low leakage: nA level
- Operating Voltage: 5V
- Low Clamping Voltage
- Complies With IEC 61000-4-2 (ESD) Immunity Test Air Discharge: $\pm 15\text{kV}$
Contact Discharge: $\pm 8\text{kV}$
- Complies With IEC61000-4-4 (EFT) 40A (5/50ns)
- Complies With IEC61000-4-5 (Lightning) 15A (8/20 μs)
- Short Lead Time
- Cross Competitors Parts and More.
- RoHS/RoHS III compliant, RoHS Annex III lead Exemption (Exempt per RoHS EU 2015/863) and Halogen Free (HF)



Image shown is a representation only.

*Exact specifications should be obtained
from the product dimension.*



APPLICATION

- USB 2.0 Power And Data Line
- Set-top Box And Digital TV
- Digital Video Interface (DVI)
- Notebook Computers
- SIM Ports
- 10/100 Ethernet

ELECTRICAL CHARACTERISTICS

- See Page 5 ~Page 6.
- All Parameters are Subject To NextGen Components' Final Confirmation

HOW TO ORDER

- Please Follow Up Part Code Guide And Indicate NextGen Part Code ESD3Z5V0CMLS3M For RFQ and Order.


PART CODE GUIDE

RFQ
[Request For Quotation](#)


CODE	NAME	KEY SPECIFICATION OPTION
ESD3Z	Product Series Code	SMD Transient Voltage Suppressors (TVs) Diodes, Case SOD-323, 2 Pads, Bi-Directional Type
5V0CM	Parameters Code	Letter or Digits (A~Z, a~z or 0~9)
LS	Internal Control Code	Letter or Digits (A~Z, a~z or 0~9)
3M	Marking Code	Marking "3M"
XX	Special/Custom Parameters Code	Letter or Digits (A~Z, a~z or 0~9) for Special Parametric; Blank: N/A

DIMENSION- Unit: mm (inch), Case SOD-323 Outline

Top View




Side View




SYMBOL	MM			INCH		
	MIN.	Nom.	MAX.	MIN.	Nom.	MAX.
A	0.80	0.90	1.00	0.031	0.035	0.040
A1	0.00	0.05	0.10	0.000	0.002	0.004
A3	0.15 REF			0.006 REF		
B	0.25	0.32	0.40	0.010	0.012	0.016
C	0.089	0.12	0.177	0.003	0.005	0.007
D	1.60	1.70	1.80	0.062	0.066	0.070
E	1.15	1.25	1.35	0.045	0.049	0.053
L	0.08			0.003		
HE	2.30	2.50	2.70	0.090	0.098	0.105

Recommend Pad Layout



Pin Configuration



SYMBOL	F	G	J	K
Unit (Inch)	0.063	0.112	0.033	0.025
Unit (mm)	1.60	2.85	0.83	0.83

MECHANICAL CHARACTERISTICS

CASE	UL FLAMMABILITY CLASSIFICATION RATING	TERMINALS	MARKING
JEDEC SOD-323 molded plastic body	UL 94V-0	High Temperature Soldering Guaranteed: 260°C/ 10s,	3M

ABSOLUTE MAX. RATING & CHARACTERISTICS - TA=25°C unless otherwise specified, For Reference Only

PARAMETER	SYMBOLS	VALUE	UNITS
Peak Pulse Power (8/20μs)	P _{pp}	320	W
ESD per IEC 61000-4-2 (Air)	V _{ESD}	±15	Kv
ESD per IEC 61000-4-2 (Contact)		±8	
Operating Temperature Range	T _J	-55 ~ +125	°C
Storage Temperature Range	T _{STJ}	-55 ~ +150	°C

ELECTRICAL CHARACTERISTICS - TA=25°C unless otherwise specified, For Reference Only

PARAMETER	TEST CONDITION	SYMBOLS	VALUE			UNITS
			MIN.	TYP.	MAX.	
Reverse Working Voltage		VRWM			5.0	V
Reverse Breakdown Voltage	IT = 1.0mA	VBR	6.0			V
Reverse Leakage Current	VRWM = 5.0V	IR			0.1	μA
Clamping Voltage	IPP = 1A, tp = 8/20μs	VC			9.8	V
	IPP = 4A, tp = 8/20μs		15		17	V
Junction Capacitance	VR = 0V, f = 1MHz	Cj	-	11	-	pF

RATINGS AND CHARACTERISTICS CURVES- For Reference Only, $T_a=25^{\circ}\text{C}$ Unless Otherwise Specified.

Fig1. 8/20 μs Pulse Waveform







Fig2. ESD Pulse Waveform (according to IEC 61000-4-2)



RATINGS AND CHARACTERISTICS CURVES- For Reference Only, $T_a=25^{\circ}\text{C}$ Unless Otherwise Specified.


Fig3. Power Derating Curve



RECOMMENDED SOLDERING PARAMETERS – FOR REFERENCE ONLY


PROFILE FEATURE		PB-FREE ASSEMBLY
Average Ramp-up Rate (T_L Max to T_p)		3°C/second Max
Preheat	Temperature Min (T_s Min.)	150°C
	Temperature Max (T_s Max.)	200°C
	Time (t_s Min. to t_s Max.)	60 ~ 180 seconds
Time maintained above	Temperature (T_L)	217°C
	Time (t_L)	60 ~ 150 seconds
Peak/Classification Temperature (T_p)		260 °C
Time within 5°C of actual Peak Temperature (t_p)		10 seconds Max.
Ramp-down Rate		6 °C /Second Max.
Time 25 °C to Peak Temperature		8 Minutes Max.
Suggest reflow times		3 Times Max.

TAPE/REEL - Unit: mm, All Devices are packed in accordance with EIA standard RS-481-A and specifications



ITEM	SYMBOL	TOLERANCE	SOD-323
Carrier width	A	0.1	1.46
Carrier Length	B	0.1	2.9
Carrier Depth	C	0.1	1.25
Sprocket hole	d	0.05	1.55
7"Reel outside diameter	D	2	178
7"Reel inner diameter	D1	Min.	50
Feed hole diameter	D2	0.5	13
Sprocket hole position	E	0.1	1.75
Punch hole position	F	0.1	3.5
Punch hole pitch	P	0.1	4
Sprocket hole pitch	P0	0.1	4
Embossment center	P1	0.1	2
Overall tape thickness	T	0.1	0.06
Tape width	W	0.3	8
Reel width	W1	1	12.3
Qty. Per Reel (pcs)	3000		

IMPORTANT NOTES AND DISCLAIMER

1. **ROHS COMPLIANCE:** The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU RoHS Directive (EU) 2015/863 EC (RoHS3). RoHS Test Report for this product can be obtained at Download Center.
2. **REACH COMPLIANCE:** REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, REACH Test Report for this product can be obtained at Download Center.
3. All Product parametric performance is indicated in the Electrical Characteristics for the listed herein test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.
4. NextGen Component, Inc (*NextGen*) reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
5. *NextGen* makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does *NextGen* assume any liability for application assistance or customer product design.
6. *NextGen* does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application. No license is granted by implication or otherwise under any intellectual property rights of NextGen.
7. *NextGen* products are not authorized for use as critical components in life support devices or systems without express written approval by *NextGen*.
8. *NextGen* requires that customers first obtain an RMA (Returned Merchandise Authorization) number prior to returning any products. Returns must be made within 30 days of the date of invoice, be in the original packaging, unused and like-new condition. At the time of quoting or purchasing, a product may say that it is Non-Cancelable/ Non-Returnable (NCNR). These products are not returnable and not refundable.