

FILM CAPACITORS – AC motor capacitor

PART NO.: C65AR6606J6600D3304

YUHUA ELECTRICAL

CBB65 Series, 370VAC, 60 μ F, $\pm$ 5% , -40°C~70°C , Radial, D55*H100mm

Date: 9/18/2026

Version: 2.0

AUTHORIZED DISTRIBUTOR

NextGen Components, Inc.


USA Office and Warehouse Location: 9 Orchard Road, Suit 106, Lake Forest, CA 92630, USA

RFQ/Order Support: sales@NextGenComponent.com

Note: This page was created by NextGen Components, Inc. ("NextGen"). The attached last document was created by the part manufacturer, not NextGen, and is provided strictly 'as is.' NextGen, its subsidiaries, affiliates, employees, and agents make no representations or warranties regarding the attached last document and disclaim any liability for the consequences of relying on the information therein. All referenced brands, product names, service names, and trademarks are the property of their respective owners.

■ PART NUMBER GUIDE

The 19 digits part number is formed as follow:



■ PRODUCT PICTURE




■ TYPICAL APPLICATION

1. Applicable to startup and operating of the compressor of air-conditioning and refrigerator.

■ FEATURES

1. Low loss, high insulation resistance;
2. Excellent self-healing and high stability;
3. Small volume and withstand high voltage;
4. Built-in explosion-proof device, reliable safety performance.

■ OUTLINE DRAWING



The example of Marking:

YUVA® 370VAC (RoHS)
 60 μ F $\pm$ 5% 50/60Hz
 40/70/21 S2 B SH
YU® CBB65-A
 Protected
 E317866 10 000 AFC
 Ningguo Yuhua

■ TECHNICAL REQUIREMENTS

Item No	Product code	Rated capacitance	Rated voltage	Outline size		
				D	D1	H
101050005	C65AR6606J6600D3304	60 μ F	370V	55	58	100

1. The capacity of allowable deviation: $\pm 5\%$;
2. Test voltage: Between two electrodes: Two times of rated voltage, 2S; Between electrode and shells: 2000V~, 2S;
3. Insulation resistance: Between pole-shell $\geq 2000M\Omega$;
4. Dissipation factor: $\text{tg}\delta \leq 0.0020$ (100Hz);
5. Life: 370V ~ , B, security level is S2;
6. Terminals: 250# (2+2);
7. Using a sticky label about the identification, climate type and etc according to the certification marks;
8. The production date and batch number are laser engraved on the bottom of the product.